Trasmettitore di Peso **DAT 700 CANopen**

Informazioni generali

PWS38520261106

Il trasmettitore di peso DAT 700 riscrive il concetto di prestazioni elevate ad un piccolo prezzo; questo trasettitore di peso è pratico, compatto, configurabile tramite tasti a pannello oppure attraverso il software Optimation che è in grado di garantire upload e download delle configurazioni oltre alla visione dei filtri in real time. Il trasmettitore di peso DAT 700 è disponibile in versione seriale e/o analogica oppure bipolare. Diversi Fieldbus sono disponibili tramite modulo esterno. **Le celle di carico collegabili a questo trasmettitore sono analogiche e/o amplificate in tensione ed in corrente.**



Software Optimation 1.11.22: optimation_weighing_software.zip

Manuale Tecninco ENG: dat-700_technical_manual.pdf

Manuale d'installazione ENG: dat-700_installation_manual.pdf

Tutti i dati indicati possono essere soggetti a variazione senza preavviso.
Tutte le misure indicate sono espresse in millimetri (mm).

Specifiche tecniche

PWS38520261106

Alimentazione elettrica:	10-30VDC protected against reverse polarity, protection with resettable fuse
Isolante:	Class II
Temperatura d'esercizio:	-10°C ± +40°C (max. non-condensing humidity 85%)
Temperatura di stoccaggio:	-20°C ± +60°C
Display:	numerical 6-digit red 7-segment led (h 14 mm)
Dimensioni:	96 mm x 48 mm x 100 mm (w x h x d) (terminal blocks included)
Materiale:	self-extinguishing PPO (UL 94 V0)
Connessione elettrica:	removable screw 5.08 mm pitch terminal blocks
Cell input:	max 8 of 350 ohms in parallel
Tensione di lavoro:	5Vdc (cell input), ± 10 V / ± 5 V (analog voltage output), 0 ± 20 mA / 4 ± 20 mA (current analog output)
Linearità uscita:	< 0.01% of full scale (cell input), 0.03% of full scale (current analog & analog voltage output)
Deriva in temperatura (ingresso):	< 0.001% of full scale / C° (cell input), 0.002% of full scale / °C (current analog & analog voltage output)
Risoluzione interna:	24 bits (cell input), 16 bits (current analog & analog voltage output)
Campo di misura:	from -7.6 mV/V to +7.6 mV/V
Filtro:	selectable 0.1 Hz - 1000 Hz
Range decimali impostabili:	0 to 4 decimal digits
Uscite logiche:	2 photo relay outputs (24 VDC/Vac one NO contact) Relay contact rating 100 mA
Ingressi logici:	no. 2 opto-isolated
Porte seriali:	Rs232 half duplex, Rs485 half-duplex, USB Device for instrument programming and setting
Baud rate:	up to 115 kb/s (default 9600 b/s)
Fieldbus:	PROFIBUS DP-V1, PROFINET, CANOPEN, ETHERNET IP, ETHERCAT, ETHERNET (with external module)
Calibrazione:	digital from buttons (current & analog voltage output)
Impedenza:	minimum 10K Ohm (current analog output), maximum 300 Ohm (analog voltage output)
Microcontrollore:	32-bit ARM Cortex M0+, 256KB Flash reprogrammable on-board by USB
Memoria dati:	32 Kbytes + optional Aliby memory (1MByte)
Conformità alle normative:	EN61000-6-2, EN61000-6-3 for EMC, EN61010-1 for Electrical Safety

Tutti i dati indicati possono essere soggetti a variazione senza preavviso.
Tutte le misure indicate sono espresse in millimetri (mm).

Product Code	Product Model
PSDA0070	DAT 700 BASIC
PSDA0700	DAT 700 ANALOG
PSDA7001	DAT 700 PROFIBUS
PSDA7002	DAT 700 PROFINET
PSDA7003	DAT 700 ETHERNET IP
PSDA7004	DAT 700 ETHERNET
PSDA7005	DAT 700 ETHERCAT
PSDA7006	DAT 700 CANOPEN
PSDA7007	DAT 700 ANALOG + PROFIBUS
PSDA7008	DAT 700 ANALOG + PROFINET
PSDA7009	DAT 700 ANALOG + ETHERNET IP
PSDA7010	DAT 700 ANALOG + ETHERNET
PSDA7011	DAT 700 ANALOG + ETHERCAT
PSDA7012	DAT 700 ANALOG + CANOPEN
PSDA7013	DAT 700 version INPUT VOLT BASIC
PSDA7014	DAT 700 version INPUT VOLT ANALOG
PSDA7015	DAT 700 version INPUT VOLT PROFIBUS
PSDA7016	DAT 700 version INPUT VOLT PROFINET
PSDA7017	DAT 700 version INPUT VOLT ETHERNET IP
PSDA7018	DAT 700 version INPUT VOLT ETHERNET
PSDA7019	DAT 700 version INPUT VOLT ETHERCAT
PSDA7020	DAT 700 version INPUT VOLT CANOPEN
PSDA7021	DAT 700 version INPUT VOLT ANALOG + PROFIBUS
PSDA7022	DAT 700 version INPUT VOLT ANALOG + PROFINET
PSDA7023	DAT 700 version INPUT VOLT ANALOG + ETHERNET IP
PSDA7024	DAT 700 version INPUT VOLT ANALOG + ETHERNET
PSDA7025	DAT 700 version INPUT VOLT ANALOG + ETHERCAT
PSDA7026	DAT 700 version INPUT VOLT ANALOG + CANOPEN
PSDA7027	DAT 700 version INPUT mA BASIC
PSDA7028	DAT 700 version INPUT mA ANALOG
PSDA7029	DAT 700 version INPUT mA PROFIBUS

Tutti i dati indicati possono essere soggetti a variazione senza preavviso.
Tutte le misure indicate sono espresse in millimetri (mm).

Product Code	Product Model
PSDA7030	DAT 700 version INPUT mA PROFINET
PSDA7031	DAT 700 version INPUT mA ETHERNET IP
PSDA7032	DAT 700 version INPUT mA ETHERNET
PSDA7033	DAT 700 version INPUT mA ETHERCAT
PSDA7034	DAT 700 version INPUT mA CANOPEN
PSDA7035	DAT 700 version INPUT mA ANALOG + PROFIBUS
PSDA7036	DAT 700 version INPUT mA ANALOG + PROFINET
PSDA7037	DAT 700 version INPUT mA ANALOG + ETHERNET IP
PSDA7038	DAT 700 version INPUT mA ANALOG + ETHERNET
PSDA7039	DAT 700 version INPUT mA ANALOG + ETHERCAT
PSDA7040	DAT 700 version INPUT mA ANALOG + CANOPEN
PSDA7041	DAT 700 ANALOG bipolar
PSDA7042	DAT 700 ANALOG bipolar + PROFIBUS
PSDA7043	DAT 700 ANALOG bipolar + PROFINET
PSDA7044	DAT 700 ANALOG bipolar + ETHERNET IP
PSDA7045	DAT 700 ANALOG bipolar + ETHERNET
PSDA7046	DAT 700 ANALOG bipolar + ETHERCAT
PSDA7047	DAT 700 ANALOG bipolar + CANOPEN
PSDA7048	DAT 700 version INPUT VOLT ANALOG bipolar
PSDA7049	DAT 700 version INPUT VOLT ANALOG bipolar + PROFIBUS
PSDA7050	DAT 700 version INPUT VOLT ANALOG bipolar + PROFINET
PSDA7051	DAT 700 version INPUT VOLT ANALOG bipolar + ETHERNET IP
PSDA7052	DAT 700 version INPUT VOLT ANALOG bipolar + ETHERNET
PSDA7053	DAT 700 version INPUT VOLT ANALOG bipolar + ETHERCAT
PSDA7054	DAT 700 version INPUT VOLT ANALOG bipolar + CANOPEN
PSDA7055	DAT 700 version INPUT mA ANALOG bipolar
PSDA7056	DAT 700 version INPUT mA ANALOG bipolar + PROFIBUS
PSDA7057	DAT 700 version INPUT mA ANALOG bipolar + PROFINET
PSDA7058	DAT 700 version INPUT mA ANALOG bipolar + ETHERNET IP
PSDA7059	DAT 700 version INPUT mA ANALOG bipolar + ETHERNET
PSDA7060	DAT 700 version INPUT mA ANALOG bipolar + ETHERCAT
PSDA7061	DAT 700 version INPUT mA ANALOG bipolar + CANOPEN

Tutti i dati indicati possono essere soggetti a variazione senza preavviso.
Tutte le misure indicate sono espresse in millimetri (mm).