Technical specifications

PWS16420261113


The serial converter S125 Profibus DP is used for long-distance serial connection and covers distances from 15 m to 200 m. The serial converter S125 is compliant with: EN50081-1, EN50082-2 for EMC, EN61010-1 for Electrical Safety.

Material:	NORYL UL 94 V-0 flame retardant
Degree of protection:	IP40
Temperature range:	-10°C ÷ +40°C (max umidity 85% without condensation)
Storage temperature:	-20 ÷ +50°C
Serial port:	RS422, Profibus DP
Power supply:	24 Vcc ±15%
Regulatory compliance:	EN50081-1, EN50082-2 for EMC; EN61010-1 for electrical safety
Weight:	120 g
Baud rate fieldbus:	12 Mbit/sec
Dimensions:	71mm x 90mm x 58mm (LxHxD)
Fieldbus:	Modbus
Baud rate:	34.800 bit/sec
Isolation:	Class II
Cable Lenght:	100m
Installation category:	Cat. II
Power consumption:	3 VA



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963