







Technical specifications

PWS12420260523




Measuring range:	-3,9 ÷ +3,9 mV/V
Full scale non-Linearity:	<0.01 % full scale
Gain drift:	<0.001 % of full scale/°C
Display:	Graphical 3 "
A/D Converter:	24 bits
Internal Resolution:	> 16,000,000 points
Transducer input voltage:	5 Vdc / 60 mA (max 4 350 Ohm load cells in parallel)
Degree of protection:	IP54
Visible resolution (in divisions):	50000
Divisions value (adjustable):	x1, x2, x5
Decimal figures range:	0 ÷ 3
Temperature range:	-10 ÷ +50 °C (max 85% humidity without condensation)
Storage temperature:	-20 ÷ +70 °C
Power supply:	4 AA batteries - Power consumption 5 W
Weight:	500 g
Accuracy full scale:	0.033 % full scale
Impedance:	350 ÷ 700 Ohm, 300 ÷ 4500 Ohm
Load cells connection:	25-pin D-sub connector and cable length 2m
Power consumption:	125 ÷ 190 mA
Input signal cells:	-3 ÷ +20.3 mV
Voltage power cell:	3 ÷ 12 Vdc
Connection to the instruments:	25-pin D-sub connector and cable length 0.5 m

All indicated data may be changed without notice.
 All the measures indicated are expressed in millimeters (mm).

Display visualization



All indicated data may be changed without notice.
 All the measures indicated are expressed in millimeters (mm).



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).