Thermal Printer **DP 24**

available with certification • UL

Technical specifications

PWS15020261113

DP 24 is a high-performance desktop thermal printer with an optional cutter. DP 24 thermal printer owns two-colored thermal paper. The paper- change is easy thanks to the frontal access and to the autoloading.

Internal Resolution:	203 dpi (8dots/mm)
Serial port:	RS232
Power supply:	90-240 Vac, 50/60 Hz
Regulatory compliance:	EN60950 2001
Weight:	0.6 Kg
Dimensions:	170x120x100 mm (h=110mm with cutter)
Print direction:	straight 180°
Print formats:	normale, double and quadruple height and width, reverse, underscored, italic, bold
Printing speed:	110 High Quality, 140 High Speed
Roll size:	max diameter 65mm
Paper width:	60 ±0.5 mm
Print Method:	Thermal printing
Drivers:	Win 2K, XP, Linux
Graphic memory:	3 logos of 32 KB
Flash memory:	256 KB
Data buffer:	8 KB
Emulation:	CUSTOM/POS
Character set:	ASCII standard, International
MTBF:	180.000 hours
DKD function:	1 Driver
Power consumption:	0.5 A



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963