

## Technical specifications

PWS15020260622

DP 24 is a high-performance desktop thermal printer with an optional cutter. DP 24 thermal printer owns two-colored thermal paper. The paper- change is easy thanks to the frontal access and to the autoloading.

<b>Internal Resolution:</b>	203 dpi (8dots/mm)
<b>Serial port:</b>	RS232
<b>Power supply:</b>	90-240 Vac, 50/60 Hz
<b>Regulatory compliance:</b>	EN60950 2001
<b>Weight:</b>	0.6 Kg
<b>Dimensions:</b>	170x120x100 mm (h=110mm with cutter)
<b>Print formats:</b>	normale, double and quadruple height and width, reverse, underscored, italic, bold
<b>Printing speed:</b>	110 High Quality, 140 High Speed
<b>Roll size:</b>	max diameter 65mm
<b>Paper width:</b>	60 ±0.5 mm
<b>Print Method:</b>	Thermal printing
<b>Print direction:</b>	straight 180°
<b>MTBF:</b>	180.000 hours
<b>DKD function:</b>	1 Driver
<b>Power consumption:</b>	0.5 A
<b>Drivers:</b>	Win 2K, XP, Linux
<b>Graphic memory:</b>	3 logos of 32 KB
<b>Flash memory:</b>	256 KB
<b>Data buffer:</b>	8 KB
<b>Emulation:</b>	CUSTOM/POS
<b>Character set:</b>	ASCII standard, International



All indicated data may be changed without notice.  
 All the measures indicated are expressed in millimeters (mm).