Off Center load cell **PSTA5**

available with certification • ATEX

General information

PWS17320261108

The off center load cell PSTA5, built in stainless steel, is robust and precise and has high performance at a competitive price. The single point load cell PSTA5 is ideal for large single-cell platforms. The off center load cell maintains accuracy in any position the object is loaded and this solves the problems that usually occur in weighing systems if the object does not bear exactly on the center of the cell. This type of cell is particularly used in the food packaging sector and for the construction of single-cell scales. The off center load cell PSTA5 has a 5 meter long shielded cable with 6 wires and is available with ATEX certification.



Suggested related products

A highly performing weighing system must be accurate, perfectly calibrated and well maintained. In order to improve the load cell performance and to optimize its functioning, you may need the following products:

Off Center load cell C2G1

Off Center load cell CB004

Off Center load cell CB14

Off Center load cell U2D1

All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963

Technical specifications


PWS17320261108

Rated load (RL):	100, 150, 200, 300, 360, 500 Kg
Combined error:	±0.05 % RO
Repeatability:	±0,03 % full scale
Creep (30 minutes):	±0.03 % RO
Full scale non-Linearity:	0,03 % FS/°C
Safe overload:	150 % full scale
Gain drift:	0,002 % FS/°C
Ultimate overload:	300 % full scale
Material:	Steel
Degree of protection:	IP68
Deflection:	0.2 ÷ 1.4 mm
Compensated Temperature:	-10 ÷ + 40 °C
Temperature range:	-20 ÷ + 70 °C
Temperature effect on zero balance:	±0.003 % RO/°C
Temperature effect on output:	±0.002 % output/°C
Insulation resistance:	> 2000 MOhm
Input resistance:	380 ÷ 386 Ohm
Output resistance:	350 ÷ 353 Ohm
Maximum supply voltage:	15Vdc
Hysteresis:	0,03 % FS
Zero tollerance:	1 % FS
Output tolerance:	0,1 % FS
Maximum platform size (mm):	600 x 600 (100 - 150 kg), 800 x 800 (200 - 500 kg)
Output signal:	2 mV/V
Zero thermal drift:	0,003 % FS/°C

All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

Off Center load cell **PSTA5**

available with certification • ATEX



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963