

General information

PWS1620260210

The PTS shear beam load cell, made of stainless steel, has excellent precision and linearity and it is resistant to lateral loads exceeding 50% of the rated load (RL). The PTS cell has been designed for weighing tanks, hoppers, belts, platforms, single-cell systems, suspended loads and automatic packaging machines and is usually used in the food, chemical, pharmaceutical, plastic and metallurgical sectors. The PTS shear beam load cell has a 6-meter shielded 4-conductor cable.



Suggested related products

A highly performing weighing system must be accurate, perfectly calibrated and well maintained. In order to improve the load cell performance and to optimize its functioning, you may need the following products:

Weight Transmitter DAT 1400

Weight Indicator MCT 1302

Mounting kits MKX ®

Tester 1008 TESTER 1008

Junction Box CGS4-C

Double Shear Beam Load Cell DDR


All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

Technical specifications

PWS1620260210

| | |
|--|-------------------------|
| Rated Load (RL): | 0.5, 1, 2, 5 t |
| Combined error: | ±0.023 % RO |
| Repeatability: | ±0.01 % RO |
| Creep (30 minutes): | ±0.02 % RO |
| Safe overload: | 150 % RL |
| Ultimate overload: | 300 % RL |
| Clamping force without any load: | M12= 75Nm; M18= 500Nm |
| Material: | Stainless steel |
| Degree of protection: | IP67 |
| Accuracy class: | 3000 OIML |
| Deflection: | 0.2 ÷ 1.4 mm |
| Compensated Temperature: | -10 ÷ +40°C |
| Temperature range: | -35 ÷ +65°C |
| Temperature effect on zero balance: | ±0.018 % RO/10°C |
| Temperature effect on output: | ±0.014 % on output/10°C |
| Rated output RO: | 3 mV/V ± 0.008 |
| Zero balance: | ±1 % RO |
| Insulation resistance: | > 5000 MΩ |
| Input resistance: | 350 ±3.5 Ohm |
| Output resistance: | 350 ±3.5 Ohm |
| Recommended input: | 5 ÷ 12 Vdc/ca |

All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).


Electrical Connections

| | |
|-------------|--------------|
| +Excitation | Red |
| -Excitation | Black |
| +Signal | Green |
| -Signal | White |
| Shield | Cable Shield |

| CAPACITY kg | 500-2000 | 5000 |
|-------------|----------|---------|
| | A | 130 171 |
| B | 31.32 | 36.8 |
| C | 31.32 | 36.8 |
| D | 15.7 | 19.05 |
| E | 25.4 | 38.1 |
| F | 76.2 | 95.25 |
| G | 13.4 | 20.65 |
| H | M12x1.75 | M20x2.5 |
| L | 57 | 76 |

All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).