Technical specifications

PWS16620261126


The MCWHU dynamometer is a solution designed for mobile weighing with a high capacity for industrial weighing, ideal for warehouses and more hostile environments. It is used above all in the steel, mechanical and food industry, where it is necessary to weigh significant suspended loads. The MCWHU product is equipped with a weight indicator and equipped with a wi-fi connection to communicate in real time with remote devices. The MCWHU dynamometer has a waterproof keypad with 5 keys (zero, automatic tare, mode, print and on / off), a plexiglass protective screen, a radiofrequency remote control and other options on request (hook and bell, heat shield for protection against infrared rays and high temperatures, accessories connected in radiofrequency etcetera).

Display:	red LED 40 mm
Degree of protection:	IP67
Temperature range:	-10 ÷ 80°C
Power supply:	230 Vac 50 Hz
Weight:	86 kg
Accuracy:	±0.1 % full scale




All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).


PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963



All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963





All indicated data may be changed without notice.
All the measures indicated are expressed in millimeters (mm).

PAVONE SISTEMI S.R.L.
Via Tiberio Bianchi 11/13/15, 20863 Concorezzo (MB), Milan, Italy
T (+39) 039 9162656 **F** (+39) 039 9162675 **W** pavonesistemi.com
Industrial Electronic Weighing Systems since 1963